



**Rely on us.**<sup>SM</sup>

# Varn<sup>®</sup> Absolute CA 2020

Alcohol Substitute for Sheetfed Printing

## Alcohol Substitute

Varn<sup>®</sup> Absolute CA 2020 is effective in eliminating alcohol use on sheetfed press equipment with continuous dampening systems. Use of this product will provide a wider ink-and-water window and offers variable wetting with adjustments to dosage.

### Advantages of Varn<sup>®</sup> Absolute CA 2020

- Recommended as a second-step additive to Varn Supreme CA 1010 fountain solution
- Provides variable wetting. Increasing the dosage will reduce the surface tension
- Compatible with conventional, hybrid and UV inks
- Minimizes press adjustments by providing a wide ink-and-water balance window of operation

**SHEETFED CONVENTIONAL. HYBRID. UV.**



**FlintGroup**

# Varn® Absolute CA 2020

Alcohol Substitute for Sheetfed Printing

## Specifications:

Physical state: Liquid  
Solubility in water: Complete; 100%  
Specific gravity: 1.08  
Color: Colorless  
Odor: Mild

Please refer to Safety Data Sheet for more details.

## Directions:

Start with a clean and well-flushed dampening system. Use with a quality fountain solution. Product is typically dosed from 1-4 ounces per gallon of a mixed fountain solution. Recommend starting at 1 ounce per mixed gallon and increase in 1/2 ounce per gallon increments until desired print quality is obtained. Actual use level of product will vary with press size and dampening system.

## MODE D'EMPOLI:

Commencez par un système d'amortissement propre et bien rincé. Le produit est un de remplacement d'alcool conçu pour être employé avec une solution de fontaine mélangée. Le produit est typiquement dosé de 1-4 onces par gallon d'une solution mélangée de qualité. Recommandez de commencer à 1 once par gallon mélangé et augmentez en once de 1/2 par increments de gallon jusqu'à ce que la qualité désirée d'impression soit obtenue. Le niveau réel d'utilisation de produit changera avec la taille de pression et le système d'amortissement.

## INSTRUCCIONES:

Comience con un sistema de humectación limpio. El producto es un sustituto del alcohol diseñado para ser utilizado en conjunto con una solución de fuente de alta calidad. El producto típicamente se dosifica entre 1-4 onzas por cada galón de solución de fuente mezclado. Se recomienda comenzar con 1 onza por cada galón de solución de fuente mezclado y aumente en incrementos de 1/2 onza por galón hasta que obtenga la calidad de impresión deseada. El consumo real del producto variará de acuerdo al tamaño del que se está utilizando.

## Packaging:

5-gallon pail  
55-gallon poly drum  
330-gallon tote

**Inks,  
blankets,  
chemicals  
& more**

**Rely on us™**  
to bring greater value to your pressroom.

For more information:

Flint Group  
Print Media North America  
14909 N. Beck Road  
Plymouth, MI 48170  
+1 734 781 4600  
printmedia.na@flintgrp.com

www.flintgrp.com

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. Customers are responsible for confirming suitability of this product for their application. In no event shall Flint Group be liable for any errors, facts or opinions contained herein, or any claims by any party alleging reliance on these materials, regardless of the form of action.

Product names followed by a ® are trademarks registered by a Flint Group company.

Version 5/2015 Page 2 of 2