



Rely on us.™

Varn® OverNite Deglazer

The Industry's Best Roller and Blanket Deglazer

Varn® Specialty Chemical: Cleaner & Rejuvenator

Let OverNite stand and deep clean your rollers during the night. After using a water-miscible or environmental wash to remove wet ink and glaze, lint, coating, etc., run in Varn OverNite to remove deep-seated glaze, resins and varnishes. After the deglazer has lifted the contaminants, remove the remaining deglazer and residue with a Varn® water-miscible wash mixed with 20-30% water or a Varn® environmental wash. This gives the roller and blanket surfaces a deep clean and leaves a smooth, ink-receptive surface.

Advantages of Varn® OverNite Deglazer

- Works during scheduled downtime
- Will not swell rubber
- Very low VOC
- Enhances ink receptivity of blankets and rollers

SHEETFED.



FlintGroup

Varn® OverNite Deglazer

The Industry's Best Roller and Blanket Deglazer

Specifications:

Flash Point: >200°F (93°C)
VOC (lbs/gal): 1.04
Vapor Pressure: 0.80 (mmHg@20°C)
Cleaning Strength: Strong but Mild to Rollers

Directions:

Wash up your press normally. Then run OverNite into the ink roller train for 1 or 2 minutes. Use OverNite on a cloth and wipe blankets. Let OverNite stand and deep-clean and rejuvenate your rollers and blankets overnight. Leave it on during the weekend if you choose. Wash up the press in the morning with a Varn water-miscible wash mixed with 20% -30% water or a Varn environmental wash without water. When you ink up, you'll find that your rollers and blankets carry ink and print with that "new press" quality.

Packaging:

U.S.A.	CANADA
12 x 1 Quarts	12 x 1 Liters

Inks,
blankets,
chemicals
& more

Rely on us™
to bring greater value to your pressroom.

For more information:

Flint Group
Print Media North America
14909 N. Beck Road
Plymouth, MI 48170
+1 734 781 4600
printmedia.na@flintgrp.com

www.flintgrp.com

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. Customers are responsible for confirming suitability of this product for their application. In no event shall Flint Group be liable for any errors, facts or opinions contained herein, or any claims by any party alleging reliance on these materials, regardless of the form of action.

Product names followed by a ® are trademarks registered by a Flint Group company.

Version 5/2015 Page 2 of 2