

Duco® Metal 2

Adhesive backed, two-piece can decorating blanket

For high speed 2pc can printing

Product Features

- Duco® Metal 2 has been especially designed for use on all popular two-piece can decorators.
- Its high shear strength adhesive coating allows for repeat runs with a quick and easy drum preparation. The
 precoated adhesive gives total blanket stability and virtually eliminates the risk of adhesive remaining on the
 blanket cylinder.
- Duco Metal 2's micro ground nitrile surface is suitable for varnish free polyester inks, gives minimal dot gain and reverse line detail at all operating speeds, and eliminates surface swelling.
- Duco Metal 2 is available in bespoke cut sizes, gauged and sorted to provide a maximum gauge variation of +/- o.o1mm per pack. Pack size between 8 and 50 blankets as required.
- Duco Metal 2 incorporates a high release, low density polythene (LDPE) backing. The LDPE backing prevents the
 creasing phenomenon sometimes associated with sticky backed blankets; whilst the release coating ensures
 trouble free removal.
- As pioneers of compressible structures utilising micro sphere technology, the innovative compressible layer featured within Duco blankets ensures increased durability and blanket life.

Advantages of Duco® Metal 2

- Consistent high print quality.
- Durability through multiple label changes.
- LDPE backing substrate for quick, clean removal.
- High performance adhesive for stability and clean blanket removal.





Duco® Metal 2

| Features | Benefits |
|----------------------------------|---|
| Micro ground surface. | Minimal dot gain and dense even solids, fine reverse line detail.Eliminates surface swelling. |
| High quality stabilising fabric. | Provides extra durability and robustness. |
| Thick compressible layer. | Ensures excellent recovery from smashes. |
| Dense low stretch fabric. | Provides extra stability. |
| Strong acrylic adhesive. | Added stability at speeds in excess of 2,000cpm. Minimises adhesive residue on blanket drum. |

Colour Turquoise

Face compound Nitrile polysulphide rubber blend

Surface finish Ground – Ra 1.0µm Typical

Thickness 1.96mm
Microhardness 70°

Compressibility 0.15mm @ 1060 kPa Typical / 0.26mm @ 2060 kPa Typical

Ink compatibility Two piece can decorating inks

More products. Streamlined access. Greater results.

Flint Group's Print Media division offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

 ${\it Inks and Coatings. Press room \ Chemicals. \ Blankets. \ Sleeves. \ Consumables.}$

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted. Product names followed by * are trademarks registered by Flint Group (represented by Flint Group US LLC or Flint Group Germany GmbH)