



Rely on us.SM

Varn[®] Apollo 901

Web Conditioner Designed for Retail Stocks at High Speeds

Web Conditioner

Varn[®] Apollo 901 is designed with built-in antistatic properties and improved marking protection for SNC, SCA, SCB, and lightweight coated stocks. This allows operators to control delivery and stacking of folded product at press speeds up to 3,000 fpm.

Advantages of Varn[®] Apollo 901

- Provides anti-static protection along with silicone lubrication
- Dosage can be controlled and monitored by measuring conductivity
- Allows printers to exceed performance metrics of speed, quality, and waste

HEATSET.



FlintGroup

Varn® Apollo 901

Web Conditioner Designed for Retail Stocks at High Speeds

Specifications:

Physical State: Liquid
Color: White to off white
Odor: none - very faint
Solubility in water: Emulsifies
pH ~ 8.5
 $\mu\text{mhos} \sim 85$ per ounce over water
Volatile Organic Chemicals % by wt: 0.15
VOC lb/gal: 0.01
Specific Gravity: .99
Bulk Density (lbs/gal): 8.25
Bulk Density (kg/l): 0.99

Directions:

Start at 5 ounces per gallon of water to prevent streaking, marking, and static problems. Add product at one ounce per gallon for more difficult marking and static problems. For precise measurement of dosage, check conductivity in the mixing reservoir. Product is designed to have a conductivity of 85 micromhos / oz per gallon of water.

Packaging:

U.S.A.
5 gallon pail
55 gallon drum
275 gallon tote

Inks,
blankets,
chemicals
& more

Rely on us™
to bring greater value to your pressroom.

For more information:

Flint Group
Print Media North America
14909 N. Beck Road
Plymouth, MI 48170
+1 734 781 4600
printmedia.na@flintgrp.com

www.flintgrp.com

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. Customers are responsible for confirming suitability of this product for their application. In no event shall Flint Group be liable for any errors, facts or opinions contained herein, or any claims by any party alleging reliance on these materials, regardless of the form of action.

Product names followed by a ® are trademarks registered by a Flint Group company.

Version 5/2015 Page 2 of 2