


Citokett II™

A HIGH PERFORMANCE OIL-BASED INK DESIGNED FOR FLATBED AND SEMI-ROTARY LETTERPRESS PRINTING



Citokett II™

is designed to be used in flatbed, and semi-rotary letterpress machines, provided the ink is dried with hot air or IR dryers in combination with air stream blowing on web.

Suitable for a wide variety of applications

- Self adhesive labels (coated & uncoated papers and cast coated papers)

PROPERTIES	BENEFITS
<ul style="list-style-type: none">• Excellent printability and press stability in flatbed letterpress	<ul style="list-style-type: none">• Consistent high print quality throughout press run
<ul style="list-style-type: none">• Good drying properties	<ul style="list-style-type: none">• Improved productivity
<ul style="list-style-type: none">• Enhanced colour consistency and excellent mileage	<ul style="list-style-type: none">• Improved print result and profitability

Citokett II™

Availability

- A range of Pantone® basic colours

The information contained in this brief product presentation is based on long experience of Flint Group Narrow Web and on internal standardised tests. It is not to be interpreted as a warranty or guarantee in any form as conditions beyond our control can affect the quality of the printing. If there is any doubt, the user should always make every effort to ensure that the products used are appropriate for the purpose.

- very suitable
- suitable
- usable
- not suitable

CITOKETT II™ OFFERS:

- Very good colour strength
- Good drying properties
- Very good printability
- Very good press stability
- Good adhesion to paper
- Unique characteristics for flatbed and semi-rotary printing

CITOKETT II™	
Printing speed	Up to 30 m/min
Mileage* g/m²	
Pantone®	1,8 - 2,0
Solids	1,8 - 2,5
Printability	
Process	•••
Solids	•••
Material suitability	
Paper	•••
TC thermal papers	-
TC filmic substrates	•
Filmic substrates	-
Resistance properties	
Chemical	-
Water	-
Solvent	-
Combination printing	
UV Flexo	-
UV Screen	-
UV Offset	-
UV Letterpress	-
Water-based flexo	-
UV Flexo varnish	-
Variable info printing	
Thermal overprinting	-
Thermal transfer	•
Hot foil	•
Cold foil radical	-
Laser overprinting	•
Ink jet overprinting	•
Lamination with	
Radical adhesive	-
Cationic adhesive	-

*Amount of ink in g/m² needed to obtain process density or to match Pantone® shade.

For more details on Citokett II™, call your nearest Flint Group Narrow Web office or dealer.

Flint Group Narrow Web

P.O. Box 1003,
SE-231 25 Trelleborg, Sweden
www.flintgrp.com

T +46 410 59 200
F +46 410 59 397
info.narrowweb@flintgrp.com

The aim of our technical documents is to inform our customers about general values. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that this advice document cannot be used as the basis for claims in law. Furthermore, the correct application for each product has to be checked carefully for suitability. For application details refer to Technical Data Sheet.

Product names followed by ® are trademarks registered by Flint Group Incorporated.