



Duco[®] Metal 2A

Adhesive backed, two-piece can decorating blanket

For high speed 2pc can printing

Product Features

- Duco[®] Metal 2A has been especially designed for use on all popular two-piece can decorators.
- Its high shear strength adhesive coating allows for repeat runs with a quick and easy drum preparation. The pre-coated adhesive gives total blanket stability and virtually eliminates the risk of adhesive remaining on the blanket cylinder.
- Duco[®] Metal 2A's micro ground EPDM surface provides resistance to varnishable polyester inks, and eliminates surface embossing which increases durability.
- Duco[®] Metal 2A is available in bespoke cut sizes, gauged and sorted to provide a maximum gauge variation of +/- 0.01mm per pack. Pack size between 8 and 50 blankets as required.
- As pioneers of compressible structures utilising micro sphere technology, the innovative compressible layer featured within Duco[®] blankets ensures increased durability and blanket life.

Advantages of Duco[®] Metal 2A

- Consistent high print quality.
- Durability through multiple label changes.
- High performance adhesive for stability and clean blanket removal.

Duco[®] Metal 2A

Features	Benefits
<ul style="list-style-type: none">• Micro ground surface.	<ul style="list-style-type: none">• Minimal dot gain and dense even solids.• Eliminates surface swelling.
<ul style="list-style-type: none">• High quality stabilising fabric.	<ul style="list-style-type: none">• Provides extra durability and robustness.
<ul style="list-style-type: none">• Thick compressible layer.	<ul style="list-style-type: none">• Ensures excellent recovery from smashes.
<ul style="list-style-type: none">• Dense low stretch fabric.	<ul style="list-style-type: none">• Provides extra stability.
<ul style="list-style-type: none">• Strong acrylic adhesive.	<ul style="list-style-type: none">• Added stability at speeds in excess of 2,000cpm.• Minimises adhesive residue on blanket drum.

Colour	Orange
Face compound	EPDM
Surface finish	Ground – Ra 0.7µm Typical
Thickness	1.96mm
Microhardness	65°
Compressibility	0.15mm @ 1060 kPa Typical / 0.26mm @ 2060 kPa Typical
Ink compatibility	Varnishable two piece can decorating inks (assessment recommended before use)

More products. Streamlined access. Greater results.

Flint Group's Print Media division offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks and Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

Print Media Europe
Balgray Street,
Dundee, DD3 8HN,
Scotland, UK.

T +44 (0)1382 422200
F +44 (0)1382 819051
printmedia.eu@flintgrp.com
www.flintgrp.com

The aim of our technical documents is to inform our customers about general values. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that this advice document cannot be used as the basis for claims in law. Furthermore, the correct application for each product has to be checked carefully for suitability.

Product names followed by ® are trademarks registered by Flint Group Incorporated.