

*Rely on us.*SM

dayGraphica® 3610

The ideal blanket for optimum print performance on all high speed web applications

Suitable for all high speed Heatset presses

Product Features

- dayGraphica® 3610 is one of the most durable, flexible and versatile blankets available from Flint Group. This blanket handles a broad range of printing requirements and keeps on going, whatever the age of your press.
- dayGraphica® 3610 has a ground and buffed surface finish, providing uniform gauge and a profile compatible with all of today's pressroom chemistry.
- Longer life is ensured through its high density carcass and the optimised compressible layer enables smooth, even tones and solids.

Advantages of dayGraphica® 3610

- Durable, high density carcass.
- Excellent rebound characteristics.
- Suitable for coated stocks and newsprint.

dayGraphica® 3610

Features	Benefits
<ul style="list-style-type: none">Redesigned, enhanced compressible layer.	<ul style="list-style-type: none">Compensates for press wear and variations.Provides optimal nip pressure, ensuring excellent print contrast and solid ink densities.
<ul style="list-style-type: none">High density carcass.	<ul style="list-style-type: none">Greater gauge stability for longer life.Excellent smash resistance and rebound for less waste and downtime.Specially treated fabric extends service life.
<ul style="list-style-type: none">Ground and buffed surface.	<ul style="list-style-type: none">Uniform gauge and consistency of profile.The ideal surface texture for effective ink transfer.Release characteristics reduce delamination of stocks and assists registration on lighter weight papers.
<ul style="list-style-type: none">Compatible rubber surface.	<ul style="list-style-type: none">Formulated for quick release without sacrificing print quality.Compatible with the latest pressroom chemistry.

Colour	Green
Face compound	Solvent resistant rubber blend
Surface finish	Ground – Ra 0.5µm Typical
Thickness	1.70mm
Microhardness	65°
Compressibility	0.14mm @ 1060 kPa Typical / 0.17mm @ 2060 kPa Typical
Elongation	<0.70% @ 10 N/mm
Tensile strength	>60 N/mm
Feed characteristics	Neutral
Ink compatibility	Heatset inks

More products. Streamlined access. Greater results.

Flint Group's Print Media division offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks and Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

Print Media Europe
Balgray Street,
Dundee, DD3 8HN,
Scotland, UK.

T +44 (0)1382 422200
F +44 (0)1382 819051
printmedia.eu@flintgrp.com
www.flintgrp.com

The aim of our technical documents is to inform our customers about general values. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that this advice document cannot be used as the basis for claims in law. Furthermore, the correct application for each product has to be checked carefully for suitability.

Product names followed by ® are trademarks registered by Flint Group Incorporated.