

# dayGraphica® 5200

DuraZone technology for the quality conscious sheetfed printer

### **Suitable for all Sheetfed presses**

#### **Product Features**

- Now DuraZone technology is available to sheetfed printers in a state-of-the-art offset blanket, the dayGraphica® 5200. dayGraphica® 5200 delivers the ultimate in print quality whilst providing unmatched durability. Key to this is the DuraZone compressible layer which resists smashes and gauge loss to maximise on-press life. The specially formulated face compound and smooth surface finish produce the highest dot fidelity and print contrast. Run the best run the dayGraphica® 5200.
- All dayGraphica® 5000 series blankets feature exclusive DuraZone technology, a revolutionary, next generation
  compressible layer that dramatically increases durability of offset printing blankets. DuraZone technology is the
  end result of extensive laboratory analysis and field testing, producing an ideal compressible layer that gives
  printers a productivity edge that will increase their profitability. This advanced technology enables printers to
  cut costs, reduce downtime, and keep presses running profitably.

#### Advantages of dayGraphica® 5200

- DuraZone carcass plus new surface design for sheetfed printing.
- Enhanced print quality and release.
- Dramatically reduced gauge loss.





## dayGraphica® 5200

Features	Benefits
Smooth buffed surface.	Enhances print quality and gauge control.
DuraZone compressible layer.	Better resistance to smashes and damage, longer life, faster recovery.
High density carcass.	Dramatically reduces gauge loss on installation and throughout run.
Specially formulated face compound.	Enhances print quality and release.
<ul> <li>Better match of plate and blanket surface speeds.</li> </ul>	<ul><li>Less dot gain.</li><li>Longer plate life.</li></ul>

**Colour** Purple

Face compound Solvent resistant rubber blend

Surface finish Smooth Buffed - Ra 0.5µm Typical

Thickness 1.96mm Microhardness 67°

Compressibility 0.17mm @ 1060 kPa Typical / 0.24mm @ 2060 kPa Typical

**Elongation** <0.7% @ 10 N/mm

Tensile strength >60 N/mm

Ink compatibility Conventional Sheetfed inks

#### More products. Streamlined access. Greater results.

Flint Group's Print Media division offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

#### Inks and Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

The aim of our technical documents is to inform our customers about general values. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that this advice document cannot be used as the basis for claims in law. Furthermore, the correct application for each product has to be checked carefully for suitability.

Print Media Europe Balgray Street, Dundee, DD3 8HN, Scotland, UK. T +44 (0)1382 422200 F +44 (0)1382 819051 printmedia.eu@flintgrp.com www.flintgrp.com

Product names followed by  ${\rm \rlap{I}\hskip-.05in B}$  are trademarks registered by Flint Group Incorporated.

Version: 26/09/2013 Page 2 of 2