

## Technical data sheet

Page 1 of 1

## Webking<sup>®</sup> 5060 Silk Matt Varnish

## Heatset Webking Varnishes

Characteristics	With Webking <sup>®</sup> varnish 5060 a good silk matt effect and a high rub resistance can be achieved in web offset Headsets. Webking <sup>®</sup> 5060 is suitable for area and spot printing.		
Rheological properties	Low tack		
	Low viscosity		
Press type	Suitable for high speed presses. Webking <sup>®</sup> 5060 is to be printed through the inking unit.		
Recommended substrates	SC and LWC papers		
Remarks and special information	Process temperature Recommended storage temperature Specific gravity Vapour pressure	1.0 g/cm <sup>3</sup> <10 Pa	
	barrier.	t for use for food packages without functional rrier.	
Printing properties	Good press performance Good drying properties Low misting		
Standard packaging sizes	25 – 200 - 1000 kg		

Flint Group print technicians are at your service to recommend the appropriate Hydroweb $^{\ensuremath{\$}}$  Fount Solution.

We also recommend Flint Group Washes for heatset offset presses.

Version: 20.10.2009

The aim of our technical documents is to inform and advise our customers. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that these advice documents cannot be used as the basis for claims in law.