

Novaset® 4520/50 IN PRIMER GLOSS

High quality, water-based primer for UV-inline-varnishing

Water-based coating for sheetfed offset

Product features

- Novaset® 4520/50 IN PRIMER GLOSS is a low-odour inline-primer which is used for full-surface UV-inline-varnishing via double coating units. It has been developed for non-food packaging and commercial printing and offers a good printability. In combination with a suitable UV varnish Novaset® 4520/50 IN PRIMER GLOSS allows highest gloss results and very low draw-back effect at the same time.
- Novaset® 4520/50 IN PRIMER GLOSS is suitable for both paper and board.
- Novaset® 4520/50 IN PRIMER GLOSS is suitable for single-sided coating only. In combination with a UV varnish also double-sided coating is possible.
- Novaset® 4520/50 IN PRIMER GLOSS is when used as intended and appropriately processed also suitable to be applied to the outer surface of food packaging. Mineral oil is not used as a constitutional compound of the coating.

Advantages of Novaset® 4520/50 IN PRIMER GLOSS

- Low-odour.
- Complies with the requirements for water-based coatings for food packaging.
- Leads in combination with a UV varnish to maximum gloss results.
- Very low draw-back effect.
- In combination with UV varnish suitable also for double-sided coating.

Novaset® 4520/50 IN PRIMER GLOSS

	Printing properties										
	Drying	Gloss effect	Rub protection	Anti-Sealing	Suitability for perfecting	Hot foil stamping	Barrier properties	Blister ability	Wet blocking resistance	Slip	Glueability
Novaset® 4520/50 IN PRIMER GLOSS	2	7	-	-	-	-	-	-	-	-	-
1 = Characteristic weakly expressed 7 = Characteristic strongly expressed											
<i>The assessment of the product properties was made under standardised printing conditions. In individual cases, under special conditions, as in printing with very heavy coverage of coating, the classification of certain properties may be different.</i>											

Product code	VP30-031D-#### Final 4 digits relate to pack size.
Pack sizes	125 kg (O1MA), 220 kg (O1NF), 1000 kg (O1UO)
Substrates	Suitable for coated paper and boards.
Application	Sheetfed double coating units
Film weight	5 – 10 g/m ² wet application
Drying	Physical, forced with hot air-dryer and IR-dryer
Viscosity	50 s / 4 mm DIN cup / 20 °C
Cleaning	Please clean up machine and equipment immediately with water.
Remarks	Stir well before use! Only use coatable printing inks! Resistance against alcohol and alkali required.
Storage	Protect against frost, heat and direct sunlight. Storage in original packaging at 5 ° to 30 ° Celsius.

You are welcome to contact us for further information.

Flint Group
Commercial, Publication & Sheetfed Inks
Sieglestrasse 25
70469 Stuttgart, Germany

T +49 711 98 16-0
F +49 711 98 16-700
sheetfed@flintgrp.com
www.flintgrp.com

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group (represented by Flint Group US LLC or Flint Group Germany GmbH).

Novaset® 4520/50 IN PRIMER GLOSS

Besondere Hinweise

In order to preserve low-odour properties, no additives such as retarders, defoamers or others may be added to the coating. An exemption to this rule is the addition of water to adjust the viscosity. A film weight of 5 – 10 g/m² wet application is recommended. A separate check is mandatory.

The coating shall under no circumstances be mixed or contaminated with washing water or other coatings. The coating unit must be clean. The complete system substrate-ink-coating must have reached a sufficient solidification before starting the further processing.

Further information

For further information please refer to our Technical Reviews "Processing Guideline Novaset Coatings" and "Resistance requirements for surface finishing".

More products. Streamlined access. Greater results.

Flint Group offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks & Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

Flint Group
Commercial, Publication & Sheetfed Inks
Sieglestrasse 25
70469 Stuttgart, Germany

T +49 711 98 16-0
F +49 711 98 16-700
sheetfed@flintgrp.com
www.flintgrp.com

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group (represented by Flint Group US LLC or Flint Group Germany GmbH).