

Rely on us.SM

Varn® Enviroflex Ultra Wash

Universal flexographic roller cleaner

Cleaner for Flexographic applications

Product Features

- Varn® Enviroflex Ultra Wash is a concentrated micro-emulsion roller cleaner for use on and off the machine.
- Varn® Enviroflex Ultra Wash is specifically designed for highly effective, deep cleaning of all flexographic inks and coatings from anilox rollers.
- Varn® Enviroflex Ultra Wash is recommended for use as part of a daily or weekly deep cleaning schedule to ensure anilox roller cells retain maximum volume and produce optimum performance and quality.

Advantages of Varn® Enviroflex Ultra Wash

- Formulated using a blend of environmentally friendly ingredients.
- Special blend of low odour, powerful cleaning agents.
- Non corrosive.
- Effective removal of solvent, water based and UV inks and coatings.
- Versatile product for roller and press cleaning applications.



FlintGroup

Varn® Enviroflex Ultra Wash

Features	Benefits
<ul style="list-style-type: none"> • Deep cleaning. 	<ul style="list-style-type: none"> • Consistent high print quality. • Clean anilox roller cells.
<ul style="list-style-type: none"> • Easy to use. 	<ul style="list-style-type: none"> • Environmentally friendly and cost effective.
<ul style="list-style-type: none"> • No vapour released. 	<ul style="list-style-type: none"> • Better working environment. • User friendly.
<ul style="list-style-type: none"> • Effectively removes ink on contact. 	<ul style="list-style-type: none"> • Prolonged cell volumes.

Application	Aqueous Based Ink	Solvent Based Ink	UV Ink
Anilox Rollers	✓	✓	✓
Ink Metering Systems	-	-	-
Impression Cylinders	✓	✓	✓
Press Frames	✓	✓	✓
Nip Rollers	✓	✓	✓
Path Rollers	✓	✓	✓
Rewind Drums	✓	✓	✓
Ancillary Cleaning Equipment	-	-	-
Printing Plates	-	-	-

Product code

KV60-1UWG-#### (final 4 digits relate to pack size).

Pack sizes

1 litre (01AF) and 20 litres (01H5).

Application

Apply Varn® Enviroflex Ultra Wash with a sponge, cloth, brush, pad or sprayer. Allow Varn® Enviroflex Ultra Wash to remain for a few minutes. Scrub the surface (the Varn® Enviroflex Pad is recommended for optimum performance). Wipe away any residue and flush the surface with water or remove with a clean cloth.

Varn® Enviroflex Ultra Wash should be used diluted down to the optimum concentration by hand or via a dosing system.

Suggested dilution rates: Use at 1:9 dilution for general cleaning.
Use at 1:2 dilution for heavy duty cleaning.
Use undiluted for heavily soiled areas.

More products. Streamlined access. Greater results.

Day International, a Flint Group Company, offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Pressroom Chemicals. Blankets. Sleeves and Cleaners.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group (represented by Flint Group Packaging Inks North America Holding LLC, Day International, Inc. Varn International Inc. or Flint Group Germany GmbH)

Flint Group
Day International UK Ltd
Varn House, Brinell Drive,
Northbank Industrial Park, Irlam,
Greater Manchester, M44 5BL, UK.

T +44 (0)161 775 5412
dayinternational.eu@flintgrp.com
www.flintgrp.com