

Rely on us.SM

Varn® Enviroflex™ Solwash

The ultimate in powerful flexo/gravure cleaning

Cleaner for Flexographic applications

Product Features

- Varn® Enviroflex Solwash is a blend of extremely powerful ink removing solvents specially formulated for the easy removal of solvent based inks and coatings.
- Varn® Enviroflex Solwash is designed to thoroughly deep clean and rejuvenate anilox rollers either on or off the press, optimizing anilox roller life and press performance.
- Varn® Enviroflex Solwash is recommended for use undiluted as part of a weekly or monthly deep cleaning schedule and rejuvenation of anilox rollers on or off press.

Advantages of Varn® Enviroflex Solwash

- Very strong solvency.
- Effective removal of solvent inks and coatings.
- Suitable for regular deep and thorough cleaning maintenance applications.
- Formulated for OEM cylinder cleaning equipment.
- Non-corrosive.
- Flashpoint between 37.8°C (100°F) and 61°C (142°F).
- Environmentally compliant and fully biodegradable.



FlintGroup

Varn® Enviroflex™ Solwash

Features	Benefits
<ul style="list-style-type: none"> Environmentally friendly formula. 	<ul style="list-style-type: none"> Ease of handling and disposal.
<ul style="list-style-type: none"> Dramatically reduces cleaning time. 	<ul style="list-style-type: none"> Quicker washup times resulting in less down time.
<ul style="list-style-type: none"> Formulated for OEM cylinder cleaning equipment. 	<ul style="list-style-type: none"> No erosion/corrosion to critical parts of the press surface.
<ul style="list-style-type: none"> Ensures anilox roller cells & gravure cylinders are 100% clean. 	<ul style="list-style-type: none"> Standardized ink film thickness and print quality.

Application	Aqueous Based Ink	Solvent Based Ink	UV Ink
Anilox Rollers	-	✓	-
Ink Metering Systems	-	✓	-
Impression Cylinders	-	✓	-
Press Frames	-	-	-
Nip Rollers	-	-	-
Path Rollers	-	-	-
Rewind Drums	-	-	-
Ancillary Cleaning Equipment	-	✓	-
Printing Plates	-	-	-

Product code

KV25-020U-#### (final 4 digits relate to pack size).

Pack sizes

5 gallon pail (01FX) and 55 gallon drum (01N4)

Application

Varn® Enviroflex Solwash should be used undiluted. Apply Varn® Enviroflex Solwash with a sponge, cloth, brush, pad or sprayer. Allow Varn® Enviroflex Solwash to remain for a few minutes. Scrub the affected area (the Varn® Enviroflex Pad is recommended for optimum performance). Wipe away any residue and flush the surface with water or remove with a clean cloth.

Varn® Enviroflex Solwash can be pumped or circulated through entire ink metering systems.

For optimum performance, use in conjunction with the Varn® Enviroflex Pad.

More products. Streamlined access. Greater results.

We offer a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Pressroom Chemicals. Blankets. Sleeves. Consumables.

You are welcome to contact us for further information.

T +1 800 321 1618
 info@flintgrp.com
 www.flintgrp.com



The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted. Product names followed by ® are trademarks registered by Flint Group (represented by Flint Group Packaging Inks North America Holding LLC, Day International, Inc. Varn International Inc.